

field matches the fabric being verified. If the chain is not valid, the procedure terminates as failed.

12. Proceed with cross-referencing device data with the Distributed Compliance Ledger's data, according to the following cases:

a. If the **VIDVerificationStatement** field was present in the entry in **Fabrics** whose **VendorID** is being verified:

i. Find the **VIDVerificationStatement** signer according to the following steps:

A. Validate the **statement_version** octet of the **VIDVerificationStatement**, ensuring it is the known value **0x21**, otherwise the procedure terminates as failed.

B. Extract the **vid_verification_signer_skid** field from the **VIDVerificationStatement**.

C. If the **VVSC** field of the **NOCs** attribute entry whose **FabricIndex** field matches the fabric being verified is present, then extract that certificate as the **VIDVerificationSignerCertificate**. Otherwise, look up the entry in the **Operational Trust Anchors Schema** under the expected **VendorID** (**VID field**) being verified whose **IsVIDVerificationSigner** field is true and whose **SubjectKeyID** matches the **vid_verification_signer_skid** field value as the **VIDVerificationSignerCertificate**. If **VIDVerificationSignerCertificate** is not found or empty after this step, then the procedure terminates as failed.

ii. Validate that the **SubjectKeyID** of the **VIDVerificationSignerCertificate** from the previous step matches the value of the **vid_verification_signer_skid**. If it does not match, the procedure terminates as failed.

iii. Validate the path of **VIDVerificationSignerCertificate** using the certificates in the **Operational Trust Anchors Schema** under the expected **VendorID** (**VID field**) being verified. If the path is invalid (e.g. any element of the chain missing, any certificate malformed, any signature verification fails, etc), then the procedure terminates as failed. Only the self-signed certificates among the set SHALL be considered as trust anchors during certificate path validation. The path length SHALL NOT be longer than 3. The verifier MAY apply knowledge of revoked entities obtained from outside the Distributed Compliance Ledger.

iv. Locally generate the **vid_verification_statement_tbs** message as described in [Section 6.4.10.3, "Generation of the vid_verification_statement_tbs message"](#). The **version** to use SHALL be the value from the **VIDVerificationStatement**. The **vid_verification_signer_skid** to use SHALL be the one from the **VIDVerificationStatement**.

v. Validate that **Crypto_Verify(vid_verification_signer_pk, vendor_id_verification_tbs, signature)** succeeds, otherwise the procedure terminates as failed.

- **vid_verification_signer_pk** is the subject public key extracted from the **VIDVerificationSignerCertificate**.
- **vendor_id_verification_tbs** is the octet string having the value of **vid_verification_statement_tbs**.
- **signature** is the signature portion of the **VIDVerificationStatement**.

b. Otherwise (i.e. **VIDVerificationStatement** not used):

i. Look-up the entry in the **Operational Trust Anchors Schema** under the expected **VendorID** (**VID field**) being verified whose **IsRoot** field is true and whose **SubjectKeyID** matches the