

ingly, validating the signature in a Matter certificate entails its logical conversion to the corresponding X.509 certificate to recover the original **tbsCertificate** of the basic syntax signed by the Certificate Authority (CA).

```
matter-certificate [anonymous] => STRUCTURE [tag-order]
{
    serial-num [1]      : OCTET STRING [ length 0..20 ],
    sig-algo [2]        : signature-algorithm,
    issuer [3]          : LIST [ length 1.. ] OF dn-attribute,
    not-before [4]      : UNSIGNED INTEGER [ range 32-bits ],
    not-after [5]       : UNSIGNED INTEGER [ range 32-bits ],
    subject [6]         : LIST [ length 1.. ] OF dn-attribute,
    pub-key-algo [7]    : public-key-algorithm,
    ec-curve-id [8]     : elliptic-curve-id,
    ec-pub-key [9]      : OCTET STRING,
    extensions [10]     : LIST [ length 1.. ] OF extension,
    signature [11]      : ec-signature,
}
```

6.5.3. Version Number

Matter certificates SHALL only support version X.509 v3. This field is not encoded in the Matter certificate structure.

6.5.4. Serial Number

The context-specific tag **serial-num [1]** SHALL be used to identify the serial number field in the Matter certificate structure.

A Matter certificate follows the same limitation on admissible serial numbers as in [\[RFC 5280\]](#), i.e., that implementations SHALL admit serial numbers up to 20 octets in length, and certificate authorities SHALL NOT use serial numbers longer than 20 octets in length.

6.5.5. Signature Algorithm

Like an X.509 certificate, a Matter certificate SHALL include a digital signature in its signature component. The signature algorithm component of a Matter certificate specifies the cryptographic algorithm used for composing and validating the signature embedded in the signature component of the certificate. The signature algorithm SHALL match the algorithm in [Section 3.5.3, “Signature and verification”](#).

The context-specific tag **sig-algo [2]** SHALL be used to identify the signature algorithm field in the Matter certificate structure.

```
signature-algorithm => UNSIGNED INTEGER [ range 8-bits ]
```