

```
{
    ecdsa-with-sha256    = 1,
}
```

The following values SHALL be defined for **signature-algorithm**:

Table 84. Signature Algorithm Object Identifiers

Value	ASN.1 OID
1	iso(1) member-body(2) us(840) ansi-x962(10045) signatures(4) ecdsa-with-SHA2(3) ecdsa-with-SHA256(2)

6.5.6. Issuer and Subject

The context-specific tags **issuer** [3] and **subject** [6] SHALL be used to identify the issuer and the subject DN fields in the Matter certificate structure. The entries in the lists SHALL be Distinguished Names (DNs), which are described in [Section 6.5.6.1, “X.501 Distinguished Names”](#).

6.5.6.1. X.501 Distinguished Names

The Issuer Name and Subject Name components of an X.509 certificate contain DN as defined in [\[RFC 5280\]](#). The ASN.1 format of a DN is a sequence of Relative Distinguished Names (RDNs). Two distinguished names DN1 and DN2 match if they have the same number of RDNs, for each RDN in DN1 there is a matching RDN in DN2, and the matching RDNs appear in the same order in both DNs.

The RDN in an X.509 certificate may be encoded as a set of one or more DN attributes, although in practice it is usually a single DN attribute. The RDN in a Matter certificate SHALL be always a single DN attribute. Two relative distinguished names RDN1 and RDN2 match if the attribute in RDN1 matches the attribute in RDN2.

```
dn-attribute => CHOICE OF
{
    // Standard and Matter-specific DN attributes.
    // Of these, all are encoded as UTF8String except domain-component,
    // which is encoded as IA5String in X.509 form.
    common-name [1]           : STRING,
    surname [2]               : STRING,
    serial-num [3]            : STRING,
    country-name [4]          : STRING,
    locality-name [5]         : STRING,
    state-or-province-name [6] : STRING,
    org-name [7]              : STRING,
    org-unit-name [8]         : STRING,
    title [9]                 : STRING,
    name [10]                 : STRING,
    given-name [11]          : STRING,
```