

```
initials [12] : STRING,
gen-qualifier [13] : STRING,
dn-qualifier [14] : STRING,
pseudonym [15] : STRING,
domain-component [16] : STRING,
matter-node-id [17] : UNSIGNED INTEGER,
matter-firmware-signing-id [18] : UNSIGNED INTEGER,
matter-icac-id [19] : UNSIGNED INTEGER,
matter-rcac-id [20] : UNSIGNED INTEGER,
matter-fabric-id [21] : UNSIGNED INTEGER,
matter-noc-cat [22] : UNSIGNED INTEGER,
matter-vvs-id [23] : UNSIGNED INTEGER,

// Standard DN attributes when encoded as PrintableString in X.509 form
// NOTE: The tags for these SHALL be the base tags + 0x80.
common-name-ps [129] : STRING,
surname-ps [130] : STRING,
serial-num-ps [131] : STRING,
country-name-ps [132] : STRING,
locality-name-ps [133] : STRING,
state-or-province-name-ps [134] : STRING,
org-name-ps [135] : STRING,
org-unit-name-ps [136] : STRING,
title-ps [137] : STRING,
name-ps [138] : STRING,
given-name-ps [139] : STRING,
initials-ps [140] : STRING,
gen-qualifier-ps [141] : STRING,
dn-qualifier-ps [142] : STRING,
pseudonym-ps [143] : STRING,
}
```

Table 85, “Standard DN Object Identifiers” lists the context-specific tags defined for the standard DN attribute types used in Matter that can be encoded in X.509 certificates as either **UTF8String** or as **PrintableString** format. In Matter certificates, the context-specific tag is logically-ORed with **0x80** (and its name given a corresponding **-ps** suffix) to indicate that the corresponding X.509 encoding of the attribute uses the **PrintableString** format instead of **UTF8String**.

Table 85. Standard DN Object Identifiers

Tag base	Matter name base	ASN.1 OID
1	common-name	joint_iso_ccitt(2) ds(5) attributeType(4) commonName(3)
2	surname	joint_iso_ccitt(2) ds(5) attributeType(4) surname(4)