

- If present, the **matter-fabric-id** attribute's value SHALL NOT be 0 (see [Section 2.5.1, “Fabric References and Fabric Identifier”](#)).
- The subject DN SHALL NOT encode any **matter-icac-id** attribute.
- The subject DN SHALL encode exactly one **matter-rcac-id** attribute.
- The subject DN SHALL NOT encode any **matter-noc-cat** attribute.
- The subject DN SHALL NOT encode any **matter-vvs-id** attribute.
- For a [Vendor Verification Signer Certificate \(VVSC\)](#):
 - The subject DN SHALL encode exactly one **matter-vvs-id** attribute.
 - The subject DN SHALL NOT encode any **matter-node-id** attribute.
 - The subject DN SHALL NOT encode any **matter-fabric-id** attribute.
 - The subject DN SHALL NOT encode any **matter-noc-cat** attribute.
- The attributes SHALL appear in the same order in the Matter certificate and in the corresponding X.509 certificates.
- When any **matter-fabric-id** attributes are present in either the [Matter Root CA Certificate](#) or the [Matter ICA Certificate](#), the value SHALL match the one present in the [Matter Node Operational Certificate \(NOC\)](#) within the same certificate chain.
- The order of the attributes can be issuer-specific and is not enforced by Matter specifications.
- All implementations SHALL accept, parse, and handle Matter certificates with up to 5 RDNs in a single DN.
- All implementations SHALL reject Matter certificates with more than 5 RDNs in a single DN.

In addition to the above rules, the encoding constraints in [Section 6.1.1, “Encoding of Matter-specific RDNs”](#) SHALL be followed.

6.5.6.4. Matter DN Examples

In all the examples below, the long hexadecimal numbers are actually encoded as hexadecimal UTF8String in the X.509 certificates, using the scheme in [Section 6.1.1, “Encoding of Matter-specific RDNs”](#).

The following is an example of subject DN encoding for a [Matter Node Operational Certificate \(NOC\)](#). Typically, it is a list of two RDN attributes:

```
subject = [[
    matter-node-id    = 0x0102030405060708,
    matter-fabric-id = 0xFAB000000000001D
]]
```

In addition to the mandatory attributes, it may also encode other supported RDN attributes such as **common-name** and [CASE Authenticated Tags](#) as presented below: