

```
subject = [[
    common-name      = "NOC Example",
    matter-node-id   = 0x0102030405060708,
    matter-fabric-id = 0xFAB0000000000001D,
    matter-noc-cat    = 0xABCD0002
]]
```

The following subject DN example illustrates that multiple RDN attributes of the same type can be encoded. The specific order of attributes is not enforced. Note that number of RDN attributes in the **subject** field SHALL NOT exceed five:

```
subject = [[
    matter-noc-cat    = 0xABCD0004,
    matter-node-id   = 0x0102030405060708,
    matter-noc-cat    = 0xABCE0018,
    matter-fabric-id = 0xFAB0000000000001D,
    matter-noc-cat    = 0xABCF0002
]]
```

The following example illustrates an illegal subject DN due to the presence of the same **CASE Authenticated Tag** value with two different version numbers.

```
subject = [[
    matter-node-id   = 0x0102030405060708,
    matter-fabric-id = 0xFAB0000000000001D,
    matter-noc-cat    = 0xABCD0004,      # <-- Value 0xABCD, Version 0x0004
    matter-noc-cat    = 0xABCD0002,      # <-- Value 0xABCD, Version 0x0002
]]
```

The following is an example of subject DN encoding for a **Matter Root CA certificate**. In this case, the Matter Root CA certificate is not associated with a specific Matter fabric:

```
subject = [[
    matter-rcac-id = 0xCA00000000000001D
]]
```

The following is another example of subject DN encoding for a **Matter Root CA certificate**. In this case, the Matter Root CA certificate is associated with a specific Matter fabric. This DN also encodes an issuer-specific **common-name** RDN attribute:

```
subject = [[
    matter-rcac-id    = 0xCA00000000000001D,
```