

Tag	Matter Name	ASN.1 OID
6	future-extension	any valid ASN.1 OID (future extension)

These context-specific tags identify the extension entries in the **extensions** list. The type of each extension is further described in the subsections below.

6.5.11.1. Basic Constraints Extension

The basic constraints extension identifies whether the subject of the certificate is a CA and the maximum depth of valid certification paths that include this certificate.

When present, the basic constraints extension SHALL be treated as **critical** and it SHALL be marked as **critical** in the corresponding X.509 certificate. The **critical** field SHALL NOT be encoded in the Matter certificate structure.

The context-specific tag **basic-cnstr** [1] SHALL be used to identify a basic constraints extension entry in the Matter certificate **extensions** list.

```
basic-constraints => STRUCTURE [tag-order]
{
    is-ca [1] : BOOLEAN,
    path-len-constraint [2, optional] : UNSIGNED INTEGER [ range 8-bits ],
}
```

The **is-ca** field SHALL be encoded regardless of the value (**true** or **false**). The **path-len-constraint** MAY be present only when **is-ca** == **true**.

6.5.11.2. Key Usage Extension

The key usage extension defines the purpose of the key contained in the certificate.

When present, the key usage extension SHALL be treated as **critical** and it SHALL be marked as **critical** in the corresponding X.509 certificate. The **critical** field SHALL NOT be encoded in the Matter certificate structure.

The context-specific tag number **key-usage** [2] SHALL be used to identify a key usage extension entry in the Matter certificate **extensions** list.

The **key-usage** field is derived as a logical OR of all **key-usage-flag** values that apply to the corresponding public key:

```
key-usage-flag => UNSIGNED INTEGER [ range 16-bits ]
{
    digitalSignature      = 0x0001,
    nonRepudiation        = 0x0002,
    keyEncipherment       = 0x0004,
    dataEncipherment      = 0x0008,
```