

leges to an Administrative Subject during a Node's [commissioning phase](#), with the exception of commands, attributes and events identified by the Node's Commissioning Access Restriction List.

Access Control Entries contain:

- A [FabricIndex](#) scoping the entry to the [Associated Fabric](#).
- A Privilege level granted by the entry (see [Section 9.10.5.2, "AccessControlEntryPrivilegeEnum Type"](#))
 - *View*: reading or subscribing to data
 - *Operate*: writing operational data and invoking operational commands
 - *Manage*: writing configuration data and invoking configuration commands (for example, [Binding](#) and [Group](#) Clusters access)
 - *Administer*: writing administrative data and invoking administrative commands (for example, [Access Control](#) and [Commissioning](#) Clusters access)
- A list of target Clusters to which the entry applies
- A list of source Subjects to which the entry applies
- An Authentication Mode that describes the type of secure channel authentication method to which the entry's subjects apply

Access Restriction Entries contain:

- A [FabricIndex](#) scoping the entry to the [Associated Fabric](#) (entries applied during commissioning do not include a Fabric Index)
- An endpoint to which the entry applies
- A cluster to which the entry applies
- A list of restricted data model elements (attributes, commands and events) for the cluster

6.6.2.1. Subjects

The meaning of a "Subject" is primarily that of describing the source for an action, using a given authentication method provided by the Secure Channel architecture. A subject SHALL be one of:

- A passcode, identified by a Passcode ID, authenticated locally by a [PASE](#) session, during the commissioning phase.
- Note that any Passcode ID other than 0, which is the default commissioning passcode, is reserved for future use.
- Furthermore, ACL entries with a PASE authentication mode SHALL NOT be explicitly added to the Access Control List, since there is an invisible implicit administrative entry (see [Section 6.6.2.9, "Bootstrapping of the Access Control Cluster"](#)) always equivalently present on the Commissionee (but not the Commissioner) during PASE sessions.
- A source node, authenticated by a [CASE](#) session using its Operational Certificate, during the operational phase. The source node can be identified by its [Node ID](#) and/or by [CASE Authenticated Tags](#).