

a Node as a [Joint Fabric](#) Anchor. See [Section 12.2.4.2, “Anchor CAT”](#) for more details. The version number of the Anchor CAT SHALL be initially set to 0x0001.

The version number represents the current version of specific identifier value. An Administrator MAY increment the version number on any changes in the set of Nodes sharing the given tag. Version number is a monotonically increasing natural number in the range of 1 to 65535. A version number of 0 is invalid and SHALL NOT be used. On reaching the maximum value (65535), wrap-around is not supported and the tag identifier SHOULD be retired by an Administrator since version increase will no longer be possible.

When a CAT appears in the [Subjects](#) list of an Access Control Entry, it SHALL be encoded within the CASE Authenticated Tag sub-space of [Node Identifiers](#), with the upper 32 bits set to 0xFFFF_FFFD. Note that this encoding cannot appear as an operational Node ID. It is merely a sub-encoding allowing the 64-bit scalars in an Access Control Entry’s [Subjects](#) list to represent both Node IDs and CATs.

6.6.2.1.2.1. Example CASE Authenticated Tags

- Joint Fabric Administrator Tag identifier 0xFFFF, Version 0x0001
 - CAT value: 0xFFFF_0001
 - Appears in Access Control Entry [Subjects](#) list as 0xFFFF_FFFD_FFFF_0001
 - Appears in [Node Operational Certificate](#) subject under OID [1.3.6.1.4.1.37244.1.6](#) with value 0xFFFF0001
 - Would appear in X.509 certificate subject under OID [1.3.6.1.4.1.37244.1.6](#) as UTF8String FFFF0001 for signature validation purposes.
- Tag identifier 0xAB12, Version 0x0003
 - CAT value: 0xAB12_0003
 - Appears in Access Control Entry [Subjects](#) list as 0xFFFF_FFFD_AB12_0003
 - Appears in [Node Operational Certificate](#) subject under OID [1.3.6.1.4.1.37244.1.6](#) with value 0xAB120003
 - Would appear in X.509 certificate subject under OID [1.3.6.1.4.1.37244.1.6](#) as UTF8String AB120003 for signature validation purposes.
- Tag identifier 0x071C, Version 0x1074
 - CAT value: 0x071C_1074
 - Appears in Access Control Entry [Subjects](#) list as 0xFFFF_FFFD_071C_1074
 - Appears in [Node Operational Certificate](#) subject under OID [1.3.6.1.4.1.37244.1.6](#) with value 0x071C1074
 - Would appear in X.509 certificate subject under OID [1.3.6.1.4.1.37244.1.6](#) as UTF8String 071C1074 for signature validation purposes.

6.6.2.2. Wildcards

The Subjects list of an Access Control Entry MAY grant a given privilege to more than one Subject, if the Authentication Mode allows it, such as in the case of the [CASE](#) and Group Authentication Modes.