

fore require a grant of **Administer** privilege. Administrators are able to bootstrap a Node's Access Control List during the **commissioning phase** due to the **Access Control Privilege Granting algorithm** implicitly granting the **Administer** privilege to Administrative Subject Nodes over a PASE commissioning channel; this implicit privilege grant applies for the Commissioner to administer the Commissionee, but not in the opposite direction.

6.6.2.10. Action attribution

The recording of a given Interaction Model Action's attribution to a source entity is distinct from the contents of an Access Control Entry. Action Attribution SHALL be recorded against the Incoming Subject Descriptor (see [Section 6.6.6.1.3, "Incoming Subject Descriptor \(ISD\) Structure"](#)) rather than against any matched Access Control Entry's contents.

6.6.2.11. Restrictions on Administer Level Privilege Grant

Since the **Administer** privilege level grants wide access to a Node for a given Subject, it SHALL NOT be valid to have an **Administer** privilege set on an Access Control Entry, unless **AuthMode** is "CASE". For example, an **AuthMode** of "Group", which admits no source Node authentication and reduced attribution ability, SHALL NOT be used to grant **Administer** privilege.

6.6.3. Access Control List Examples

The following Access Control Lists illustrate the flexibility of codifying access control policy using concrete examples.

Upon Factory Data Reset, the Access Control Cluster is empty, having an Access Control List with no entries.

```
Access Control Cluster: {
  ACL: [],          // empty
  Extension: [],    // empty (omitted hereafter)
  ARL: []           // empty for this example (omitted hereafter)
}
```

However, the Access Control Privilege Granting algorithm behaves as if, over a PASE commissioning channel during the **commissioning phase**, the following implicit Access Control Entry were present on the Commissionee (but not the Commissioner) to grant **Administer** privilege for the entire Node.

```
Access Control Cluster: {
  ACL: [
    0: {              // implicit entry only; does not explicitly exist!
      FabricIndex: 0, // not fabric-specific
      Privilege: Administer,
      AuthMode: PASE,
      Subjects: [],
    }
  ]
}
```