

```

...
3: {
    FabricIndex: 1,
    Privilege: Operate,
    AuthMode: CASE,
    Subjects: [ 0x1111_1111_1111_1111, 0xFFFF_FFFD_ABCD_0001],
    Targets: [ { DeviceType: 0x0000_010D } ]
}
]
}

```

An Administrator wants to remove the Node with Node ID 0x3333_3333_3333_3333 from the CAT group defined by CAT identifier value of 0xABCD, as installed in the previous example.

The Administrator could follow the steps outlined below:

1. Administrator will ensure that the removed node having Node ID 0x3333_3333_3333_3333 will not receive a new NOC with an CAT identifier value of 0xABCD. Note that the node removed from the group will continue to hold existing NOC (with CAT identifier of 0xABCD and version 0x0001).
2. An Administrator updates NOCs with CAT identifier value of 0xABCD and version 0x0002 (encoded as subject 0xFFFF_FFFD_ABCD_0002) in all remaining currently reachable Nodes within the CAT group to ensure they continue to have same privilege as before. In this example, Nodes having Node IDs 0x2222_2222_2222_2222, 0x4444_4444_4444_4444 and 0x5555_5555_5555_5555 are currently reachable.
3. Node with Node ID 0x6666_6666_6666_6666 from this CAT group is a valid member but was not reachable by an Administrator at the time of this change. This Node will continue to hold existing NOC with CAT of 0xABCD_0001.
4. After updating NOCs of all reachable Nodes, the Administrator SHOULD revise the Access Control Entry of all reachable nodes who have the previous CAT (encoded as subject 0xFFFF_FFFD_ABCD_0001) in an ACL entry, to remove privilege from the Node no longer in the grouping (i.e. those with version 0x0001) by increasing trusted version value to be higher than 0x0001. The Administrator decides to increment version value by one to set the new version value to be 0x0002.
5. Once ACL changes are propagated to all controlled nodes, they will no longer allow access privileges to any Node with older version (i.e. value less than 0x0002) of CAT identifier value 0xABCD. Hence, the node removed from the group, having Node ID 0x3333_3333_3333_3333 and CAT with identifier 0xABCD and version of 0x0001, can no longer access any of the controlled nodes whose ACL entries were updated to have a subject of 0xFFFF_FFFD_ABCD_0002 (CAT identifier value 0xABCD, version 0x0002).
6. Node having Node ID of 0x6666_6666_6666_6666 will not be able to access any Nodes by relying on CAT, since it does not have an NOC with latest CAT (with version 0x0002). However, it can still access Nodes that list it as a subject Node ID explicitly. When an Administrator eventually establishes connection to this Node, the Administrator SHOULD update the NOC to the latest version, with CAT set to 0xABCD_0002. After having its NOC updated to have the newest version of the