

```
# Subject must match, or be "wildcard"
if is_empty(acl_entry.Subjects):
    # Precondition: only CASE and Group auth can have empty subjects
    assert(acl_entry.AuthMode in [AuthModeEnum.CASE, AuthModeEnum.Group])
    # Empty is wildcard, no match required
else:
    # Non-empty requires a match
    matched_subject = False
    for acl_subject in acl_entry.Subjects:
        for isd_subject in subject_desc.Subjects:
            if subject_matches(acl_subject, isd_subject):
                matched_subject = True
                break
        if matched_subject: break
    if not matched_subject: continue

# Target must match, or be "wildcard"
if is_empty(acl_entry.Targets):
    # Empty is wildcard, no match required
else:
    # Non-empty requires a match
    matched_target = False
    for target in acl_entry.Targets:
        # Precondition: target cannot be empty
        assert(target.Cluster != null or target.Endpoint != null or target.DeviceType
!= null)
        # Precondition: target cannot specify both endpoint and device type
        assert(target.Endpoint == null or target.DeviceType == null)
        # Cluster must match, or be wildcard
        if target.Cluster != null and target.Cluster != cluster_id:
            continue
        # Endpoint must match, or be wildcard
        if target.Endpoint != null and target.Endpoint != endpoint_id:
            continue
        # Endpoint may be specified indirectly via device type
        if target.DeviceType != null and not
endpoint_contains_device_type(endpoint_id, target.DeviceType):
            continue
        matched_target = True
        break
    if not matched_target: continue
```