

```
    if arl_restriction.Type == AccessRestrictionTypeEnum.AttributeWriteForbidden and
request_type == RequestTypeEnum.AttributeWrite:
    # if the attribute id is NULL (wildcard) or matches the cluster_element
    if arl_restriction.ID == NULL or arl_restriction.ID == cluster_element:
        # then no granted privileges
        return True

    if arl_restriction.Type == AccessRestrictionTypeEnum.CommandForbidden and
request_type == RequestTypeEnum.CommandInvoke:
    # if the command id is NULL (wildcard) or matches the cluster_element
    if arl_restriction.ID == NULL or arl_restriction.ID == cluster_element:
        # then no granted privileges
        return True

    if arl_restriction.Type == AccessRestrictionTypeEnum.EventAccessForbidden and
request_type == RequestTypeEnum.EventRead:
    # if the event id is NULL (wildcard) or matches the cluster_element
    if arl_restriction.ID == NULL or arl_restriction.ID == cluster_element:
        # then no granted privileges
        return True

return false

def get_access_status(
    acl, arl_attr, commissioning_arl_attr,
    request_privilege, subject_desc, request_type, endpoint_id, cluster_id,
    cluster_element) -> access_status:
    granted_privileges = get_granted_privileges(acl, subject_desc, endpoint_id,
    cluster_id)

    if request_privilege in granted_privileges:
        # Select the correct source of ARL depending on context.
        arl = commissioning_arl_attr if subject_desc.IsCommissioning else arl_attr
        if is_request_restricted(arl, subject_desc, request_type, endpoint_id, cluster_id,
cluster_element):
            return AccessStatusEnum.AccessRestricted
        else:
            return AccessStatusEnum.AccessGranted

    return AccessStatusEnum.AccessDenied
```