

```

isd.FabricIndex = sessions_metadata.get_fabric_index(session_id) # may be zero
else if sessions_metadata.get_auth_mode(session_id) == AuthModeEnum.CASE:
    isd.IsCommissioning = sessions_metadata.get_fabric_index(session_id) ==
sessions_metadata.get_pending_fabric_index()
    isd.AuthMode = AuthModeEnum.CASE
    isd.Subjects.append(sessions_metadata.get_src_node_id(session_id))
    # CASE session may contain CATs which also serve as subjects
    # Append all CATs if present (can be up to 3)
    if sessions_metadata.has_src_case_authenticated_tags(session_id):

isd.Subjects.append(sessions_metadata.get_src_case_authenticated_tags(session_id))
    isd.FabricIndex = sessions_metadata.get_fabric_index(session_id)
    assert(isd.FabricIndex != 0) # cannot be zero
else if sessions_metadata.get_auth_mode(session_id) == AuthModeEnum.Group:
    # Message is assumed to have been decrypted and matched properly prior to
    # this procedure occurring.
    group_id = message.get_dst_group_id()
    group_key_id = sessions_metadata.get_group_key_id(message)
    # Group membership must be verified against Group Key Management Cluster
    if group_key_management_cluster.group_key_map_has_mapping(group_id, group_key_id):
        isd.AuthMode = AuthModeEnum.Group
        isd.Subjects.append(group_id)
        isd.FabricIndex = sessions_metadata.get_fabric_index(message)
        assert(isd.FabricIndex != 0) # cannot be zero
else:
    # Do nothing on error, ISD remains unchanged
    assert(isd.IsCommissioning == False)
    assert(isd.AuthMode == AuthModeEnum.None)
    assert(is_empty(isd.Subjects))
    assert(isd.FabricIndex == 0)

return isd

```

6.6.7. Applying Privileges to Action Paths

The Data Model specifies which privilege is required for each data element, via its access qualities.

The Interaction Model specifies how each action is processed, for both its request and its response. This includes details on how the Interaction Model uses Access Control to determine whether to allow the request (i.e. continue processing), or to deny the request (and whether/how that is indicated in the response).

Determining whether to allow or deny an action for a request path entails:

- Determining the [required privilege](#) for the action, given the action, request path and type of