

7.1.4. Overview

This document defines first order elements and namespace of the data model and can also be called the meta-model (of the data model). This document is the "read me first" specification in the data model. This data model is ultimately implemented in the application layer of a communication stack.

This specification does not define how data is stored, encoded or what interactions are allowed on the data.

7.1.5. Glossary

Term	Description
MS	Manufacturer or Vendor Specific
N/A	not applicable
desc	see detailed description section

7.1.6. Conventions

See the [Conventions](#) section for conventions used in the Data Model specifications.

7.2. Data Qualities

[Cluster](#) specifications and [device type](#) definitions have tables that define the qualities of elements that make up the cluster or device type. Not all elements have all qualities. For example, a command does not have the read quality. Some elements have intrinsic qualities, that are not listed. For example, an event always has the read quality. Qualities SHALL be defined in columns in tables that describe data model elements.

7.2.1. Common Data Table Columns

The following columns are common across tables describing attributes, commands, events and structs:

ID

Defines an identifier for the data model element that is unique at its context.

Name

Defines a CamelCase name of the element to be used in specification text, not the protocol. Text usage SHALL always be followed with the element name (e.g. CurrentLevel attribute, Stopped event, or Left field).

Field

Same as **Name**. Other headers like "Field", "Bit Field", and "Command Field", are deprecated. Use **Name**.