

Conformance Column	Name	Summary
<i>C.an</i>	Choice	Exclusive choices between a number of elements with the same conformance

7.3.1. Operands in Conformance

Supported operands in a conformance expression are:

- feature code
- element in the same table (e.g. attribute, field or value)
- element in the attribute table when annotated according to [Section 7.3.13, “Expressions and Optionality”](#) (e.g. attribute, field or value)
- element in the request command definition table when used as conformance for a response command definition table, when annotated according to [Section 7.3.13, “Expressions and Optionality”](#) (e.g. field or value).

7.3.2. Feature Code in Conformance

A feature code evaluates to TRUE, if the feature is supported, otherwise it SHALL evaluate to FALSE.

7.3.3. Element in Conformance

An element name, by itself, SHALL evaluate to TRUE if the element exists, otherwise it SHALL evaluate to FALSE.

NOTE

Command field as conformance SHALL only be used as element conformance when used in the context of command (request or response).

An element name MAY be used in a value conformance expression. See [Value Conformance](#) for further details.

7.3.4. Optional Conformance

Optionality with "[]" SHALL be defined for an entire expression and not for parts of an expression. Individual conformance list entries MAY define optionality with "[]", but not the entire list.

For example: The expression "[AA] & BB" is illegal, however, "[AA & BB]" or "AA & BB" is legal.

For example: The expression "AA | [BB]" is illegal, however, "[AA | BB]" or "AA, [BB]" is legal.

The tag "O" SHALL define the element as optional for the revision. "O" SHALL only be used by itself, without operators, to mean optional without dependencies, or SHALL be used in a conformance list ending in ", O", to mean otherwise optional.