

7.3.5. Provisional Conformance

The tag "P" defines the element as provisional. "P" may be used in a list, where the intended conformance or list follows the "P". If the intended conformance has not been determined, then nothing appears after the "P".

It is recommended that the intended future conformance be noted, so that when the provisional marking is removed, the intended conformance becomes the current conformance.

For example: "P, M" means provisional, but mandatory, when not provisional in the future.

For example: "P, [AA & BB]" means provisional for now, but optional if AA & BB are true, when not provisional in the future.

For example: "[AA], P" means optional for AA and provisional otherwise, where the future conformance is unknown at this time.

Each provisional element SHALL be listed in a higher level specification, that includes the data model, and data model derived specifications that use this notation.

7.3.6. Mandatory Conformance

The tag "M" SHALL define the element as mandatory. "M" SHALL only be used by itself, without operators, to mean mandatory without dependencies, or SHALL be used in a conformance list ending in ", M", to mean otherwise mandatory.

7.3.7. Disallowed Conformance

The tag "X" is used when a derived cluster removes support for some elements. The tag "X" SHALL define the element as disallowed for the revision of the derivation. "X" SHALL only be used by itself, without operators.

7.3.8. Deprecated Conformance

The tag "D" SHALL define the element as disallowed for the revision. Previous revisions MAY support this element and conformance is defined in such previous revisions. "D" SHALL only be used by itself, without operators, to mean disallowed for the current revision, or SHALL be used in a conformance list ending in ", D", to mean that now it is still allowed (based on the conformance preceding the ", D"), but it is planned to be deprecated in the future after some grace period.

7.3.9. Value Conformance

Value conformance is when the conformance of an element is defined in relation to the value of another non-changing value, which MAY be the value of another element. The following operators are used to define such value relationships, and SHALL be used when the name of another element is involved, to differentiate from [Element in Conformance](#):

Operator	Name
==	Equal