

Operator	Name
!=	Unequal
<	Less
<=	Equal or less
>	Larger
>=	Equal or larger

7.3.9.1. Range

The applicable operators can be used to define a range of values to be used for conformance if the value is within or outside the defined range. Such as $x \leq EF \ \& \ EF \leq y$ to indicate that the element is mandatory if the value of *EF* is between the values of *x* and *y* (both included) or $EF > x$ to indicate that the element is mandatory if the value of *EF* is larger than *x*.

A range conformance SHALL only be used when an actual range is defined; in cases where $x \leq EF \ \& \ EF \leq y$ is used and *x* and *y* are equal, this notation is NOT allowed and the equal operator SHALL be used instead.

7.3.9.2. Element

An element name SHALL only support evaluation as a value, when the element name identifies one of the following:

- an attribute with the Fixed quality, or
- a field of a struct when defined as the data type for an attribute with the Fixed quality, or
- a field in a command when referenced in a command payload.

NOTE

Using the name of a command field as a value SHALL only be used in the context of command (request or response).

For example: An attribute conformance of "AttributeX == TRUE", indicates mandatory if the value of AttributeX is TRUE.

For example: An attribute conformance of "AttributeX == 10", indicates mandatory if the AttributeX has the value 10.

For example: An attribute conformance of "AttributeX.MinValue == 10", indicates mandatory if the MinValue field of AttributeX has the value 10.

For example: A command field conformance, for an element in a response, of "ReferenceToCommandRequest. InputCommandField == EnumValue", indicates the field is mandatory in the response if the request has the InputCommandField set to the specific "EnumValue".

7.3.10. Exclusivity Conformance

Exclusivity occurs when the entire expression only excludes.