

A fabric-scoped ID MAY require the presence of a [fabric-index](#) data type field within the same nesting scope to indicate the fabric associated with the ID in these cases:

- If the fabric-scoped ID is not part of fabric-scoped data.
- If the fabric-scoped ID is part of fabric-scoped data with an associated fabric that is not the fabric associated with the ID.

Fabric-scoped IDs SHALL only be indicated in these elements:

- [structs](#)
- [events](#)
- [commands](#)

Where necessary, specification text SHOULD define the data to which the [fabric-index](#) applies.

7.6. Access

Data model elements have access qualities. Some elements have intrinsic access or access limitations. For example: Cluster commands or command fields are not writable.

An Access column defines access to a data model element or set of elements. This column is valid for attributes, commands, events, and nested attribute data fields.

Access Column	Description
R	Read Access
W	Write Access
R[W]	Read Access and optionally Write Access
R*W	Deprecated: use R[W]
Privileges - separate with space	
V	Read Access or Invoke Access requires View privilege
O	Read Access , Write Access , or Invoke Access requires Operate privilege
M	Read Access , Write Access , or Invoke Access requires Manage privilege
A	Read Access , Write Access , or Invoke Access requires Administer privilege
Fabric - separate with space	
F	Fabric-Scoped Access
S	Fabric-Sensitive Access
Timed - separate with space	