

Access Column	Description
T	Write Access or Invoke Access with timed interaction only

Attributes, commands, and events SHALL define their access, and SHALL include privileges in their access definition. For example: An attribute defines whether it is readable or writable, and what privileges are required to do so.

Attributes, commands, and events that do not define any privileges as access qualities SHALL be deemed to have the following:

- View privilege required for Read access,
- Operate privilege required for Write access,
- Operate privilege required for Invoke access for request commands.
- No privileges defined for response commands.

For example: An event with implicit read access or explicit 'R' access defaults to access 'R V'. An attribute with access 'RW' defaults to access 'RW VO'. A request command with implicit invoke access defaults to privilege 'O'.

Nested elements MAY define their access, but SHALL NOT include privileges in their access definition. Nested elements SHALL inherit their privileges from the next highest element in the model hierarchy. Nested elements that do not define their access SHALL inherit their access from the next highest element in the model hierarchy. For example: A data field in a struct attribute inherits its access qualities from attribute.

Elements SHALL only include the lowest required privilege for a type of access.

That means:

- An event SHALL define the single privilege required for Read access.
- A command SHALL define the single privilege required for Invoke access.
- A readable attribute SHALL define the single privilege required for Read access.
- A writable (but not readable) attribute SHALL define the single privilege (that is not View) required for Write access.
- A readable and writable attribute MAY define a single privilege (that is not View) required for both Read and Write access.
- A readable and writable attribute MAY define the View privilege as required for Read access and one other privilege (that is not View) as required for Write access.

7.6.1. Read Access

Read access means that a request for data values associated with an element SHALL be supported. This access modifier SHALL only be defined for cluster event and attribute data definitions. This access modifier SHALL NOT be defined for cluster command definitions.