

sClusters bit in **WildcardPathFlags** is set.

7.7.5. Large Message Quality

Command messages with this quality are typically larger than the minimum IPv6 MTU of 1280 bytes and cannot be transported over **MRP**. They SHALL require **TCP** for communication. Both the request command and the response command SHALL be marked with this quality if at least one of them is expected to be large. This is because they both are part of the same **Exchange** that is bound to one underlying session.

7.7.6. Non-Volatile Quality

See **Persistence**.

7.7.7. Reportable Quality

The **Subscribe interaction** supports all attribute data. This quality is supported by other interactions that only require attribute data with this quality to support interval or change reporting.

7.7.8. Quieter Reporting Quality

This quality MAY be given to attribute data that changes in a way where some of the changes are considered to have a high rate of change or where changes are not meaningful or desirable to report.

This quality can be used for fast changing attributes, where the majority of reports would have little to no value for the client (e.g. the continuous countdown of a timer in the server where the client can have a local digital twin) but where some reports may be important to synchronize the local twin, (e.g. when a countdown starts, stops or is changed). Another case where this quality can be used is for attributes that can change value for a long period (e.g. the **CurrentLevel** of a light performing a ramp with a long transition time) or where the measured value can change quite often. This prevents over-reporting of such an attribute to many subscribed clients which could lead to link degradation on bandwidth-constrained links.

Attributes with this quality SHALL specify, in the attribute description, the details of the conditions under which changes to the attribute value SHALL, SHOULD or MAY be reported.

Changes to the value under conditions other than those specified in the attribute description SHOULD NOT be reported. To ensure clients can understand the parameters related to specifics of that attribute's reporting, the description MAY include details regarding when the attribute value might change without being reported.

Attributes MAY get this quality assigned in a revision of a cluster, to limit the amount of reporting, therefore Clients SHALL generally be resilient to more reporting than constrained by the attribute description, from older revisions of the cluster.

Attribute data with this quality SHALL support **Read Access**.