

If an AtomicRequest command is received with an [Atomic Writer ID](#) which is either unavailable or not a valid [Operational Node ID](#), the server SHALL return a status code of INVALID_COMMAND.

For AtomicRequests with any RequestType:

1. If the [AttributeRequests](#) field is empty, the server SHALL return an error code of INVALID_COMMAND.
2. If the [AttributeRequests](#) field contains duplicate values, the server SHALL return an error code of INVALID_COMMAND.
3. If the [AttributeRequests](#) contains attrib-ids for attributes not supported by the server, the server SHALL return an error code of INVALID_COMMAND.

Begin Write

If the RequestType of the AtomicRequest is BeginWrite, the server SHALL attempt to begin an atomic write and return an AtomicResponse:

1. If the client is already associated with an [Atomic Write State](#) that is associated with any attributes on the same cluster and endpoint, the server SHALL return a status code of INVALID_IN_STATE.
2. If the request does not have a [Timeout](#), the server SHALL return an error code of INVALID_COMMAND.
3. Otherwise, the server SHALL return an [AtomicResponse](#):
 - a. For each attrib-id in [AttributeRequests](#), the server SHALL return a matching [AtomicAttributeStatusStruct](#) in [AttributeStatus](#):
 - i. If the client does not have sufficient privilege to write to the attribute, the [status](#) SHALL be UNSUPPORTED_ACCESS.
 - ii. If the specified attribute does not support atomic writes, the [status](#) SHALL be INVALID_COMMAND.
 - iii. If the specified attribute is currently being used by a different atomic write, the [status](#) SHALL be BUSY.
 - iv. If the server does not have enough resources to pend writes to the attribute, the [status](#) SHALL be RESOURCE_EXHAUSTED.
 - v. Otherwise, the [status](#) SHALL be SUCCESS to indicate that the attribute is available for writing.
 - b. For internal reasons, a server MAY implement atomic writes for a set of attributes with a shared resource, such that beginning an atomic write to any of the attributes in the set requires including all of the attributes in the set. If attributes other than the requested attributes are included in an atomic write, the server SHALL return statuses for those attributes as if they had been requested.
 - c. Subsequent invocations of [AtomicRequest](#) of type [Commit Write](#) or [Rollback Write](#) SHALL provide the attrib-ids returned in [AttributeStatus](#), not the attrib-ids requested in [AttributeRequests](#).
 - d. If any of the requested attributes have a [status code](#) other than SUCCESS, the [StatusCode](#) of