

- c. Return an **AtomicResponse** with the list of **attribute statuses** and an **atomic status code** of FAILURE.
5. Otherwise, if the writes would collectively violate a constraint, then the server SHALL:
 - a. Discard all pending writes to the attributes associated with the **Atomic Write State** associated with the client
 - b. Discard the **Atomic Write State** associated with the client
 - c. Return an **AtomicResponse** with the list of **attribute statuses** and an **atomic status code** of CONSTRAINT_ERROR.
6. Otherwise, the server SHALL:
 - a. Create a list of **attribute statuses** for each attribute referenced by a pending write
 - b. Attempt to apply all pending writes to the attributes in the **Atomic Write State** associated with the client:
 - i. For each pending write, write the pending value to the attribute, and store the returned status code in the **status code** field on the **attribute status** whose **AttributeID** matches the ID of the attribute.
 - ii. If any pending write fails, return an **AtomicResponse** with an **atomic status code** of FAILURE and the list of **attribute statuses**.
 - iii. Otherwise, return an **AtomicResponse** with an **atomic status code** of SUCCESS and an empty list of **attribute statuses**.
 - c. Discard the **Atomic Write State** associated with the client

Rollback Write

If the RequestType of the AtomicRequest is RollbackWrite, the server SHALL attempt to rollback any pending writes and return an AtomicResponse.

1. If the client is not associated with an **Atomic Write State** whose endpoint-no and cluster-id match the endpoint number and ID of the cluster instance handling the request, and whose set of attrib-ids match the attrib-ids requested, irrespective of order, the server SHALL return an error code of INVALID_IN_STATE.
2. Otherwise, the server SHALL:
 - a. Discard all pending writes to the attributes associated with the **Atomic Write State** associated with the client
 - b. Discard the **Atomic Write State** associated with the client
 - c. Return an **AtomicResponse** with an **atomic status code** of SUCCESS.

7.15.7. AtomicResponse Command

The AtomicResponse command is sent by a server in response to an AtomicRequest command.