

uct supporting a dynamic endpoint has visibility into the entire network (or part thereof) of simple endpoints.

A dynamic endpoint client cluster instance MAY be used to multiplex transactions to or from multiple simple device server clusters in the network. A dynamic endpoint client cluster MAY initiate interactions to many server clusters in the network. A dynamic endpoint client cluster MAY receive data from many server clusters in the network. Dynamic endpoints MAY support relationships through bindings. A dynamic device endpoint MAY support one or more external agents, outside the node stack, that manage relationships. External agents include, but are not limited to, a cloud application, a smartphone, an in-home display, or a configuration tool.

7.16.3.5. Device Type Scope

A node device type is a utility device type scoped to a node. A node device type definition SHALL support clusters that represent the entire node. An endpoint supporting a node device type is a node endpoint. A node endpoint MAY also represent the physical device or product. There MAY be more than one node endpoint on a node.

Other classes of device types are endpoint scoped device types.

7.16.4. Extra Clusters on an Endpoint

An endpoint MAY support extra clusters not mandated by the device type definition. An endpoint MAY support optional features or cluster items (attributes, commands, events, etc.), that are not mandated by the device type definition. Extra clusters, features, or cluster items, SHALL only augment, not modify, the function of the device type or clusters.

A device type definition MAY list clusters as optional, which implies they can augment the device type. Clients MAY use those clusters to augment the operation of the other clusters for the device type.

In case of clusters appearing on an endpoint which are not listed in the Cluster Requirements table of a device type definition, there may not be a well-defined standard interpretation with respect to the context of that device type, so clients MAY ambiguously interpret how, or when, the extra clusters are intended to be used. Clients MAY ignore any clusters which are not listed in the Cluster Requirements table of a device type definition when interacting with the endpoint. This is true even for clusters that would otherwise appear to a client's or server's implementer as "obvious".

7.16.5. Primary Device Type

The Primary Device Type is selected according to the following rules:

- When a device combines multiple application device types, the manufacturer SHALL choose the application device type identifier of the primary function of the device as the Primary Device Type.
- When a device has a single application device type, the manufacturer SHALL use that as the Primary Device Type.
- For devices exposing multiple application device types for which the [superset device type](#) condition holds, the superset device type of the set of device types SHALL be used as Primary Device