

Constraint	Description
<i>constraint, constraint...</i>	Defines support of a union of two or more range or limit constraints on the number of entries.
<i>list_constraint[entry_constraint]</i>	Defines <i>list_constraint</i> as a list constraint and <i>entry_constraint</i> as a constraint on the entry data type. See also list entry qualities
Character String Data Type Constraints	
<i>char_constraint{ z }</i>	Defines <i>char_constraint</i> as the string constraint in bytes and z as the maximum number of Uni-code codepoints.
Enumeration Data Type Constraints	
all	Defines that all enumeration values that are defined for the enumeration type definition are supported for interactions on the element having this constraint.
Boolean Data Type Constraints	
all	Defines that both logical values are supported for interactions on the element having this constraint.

* x, y, or z are literal values of the data type or from the [Common Literal Values](#).

Valid examples of constraints with expressions are:

- "minOf(5, elementValue)" defines the minimum of either the value 5 or the value of the element named elementValue will be used within the constraint expression.
- "min maxOf(10, elementValue)" defines the maximum of either the value 10 or the value of the element named elementValue will be used to indicate the minimum value for the constraint.
- "1 to maxOf(15, elementValue)" defines the supported range for the element to be between the value of 1 and the maximum value of either the value 15 or the value of the element named elementValue.

7.18.3.4. Numeric Constraint

The constraints of a Numeric Data Type can be defined by the value of other elements, e.g. an element constrained by minimum and maximum values defined by the associated min/max elements (attribute or data field).

These rules apply to the constraint when elements are used as constraints:

- A constraint for an element MAY use the name of an element in the Name column of the same table.
- A constraint for an element MAY use the struct field name of an element of the same table, when annotated with the name of the constraining element from the Name column, e.g. "<ConstrainingElementName>.<Field>".