

- When writing to a fabric-scoped list, the write interaction SHALL be on an [accessing fabric](#), otherwise, the write interaction SHALL fail (see [Interaction Model Specification](#)).
- For a [read](#) interaction on a list, fabric-filtering MAY be enabled.
- For a [read](#) interaction on a list, with fabric-filtering disabled, the list SHALL be reported as a full list with all entries.

For example: A fabric-scoped full list with each entry having an associated FabricIndex and Value field:

```
List = [ { FabricIndex = A, Value = 20 },
         { FabricIndex = B, Value = 30 },
         { FabricIndex = A, Value = 40 },
         { FabricIndex = B, Value = 50 },
         { FabricIndex = B, Value = 60 } ]
```

would be a fabric-filtered list when accessed with fabric B:

```
List = [ { FabricIndex = B, Value = 30 },
         { FabricIndex = B, Value = 50 },
         { FabricIndex = B, Value = 60 } ]
```

Reading a fabric-filtered list entry index 2 accessed with fabric B reports:

```
List[2] = [ { FabricIndex = B, Value = 60 } ]
```

Writing fabric-filtered list entry index 1 when accessed with fabric B:

```
List[1] = [ { FabricIndex = B, Value = 55 } ]
```

changes the full list to:

```
List = [ { FabricIndex = A, Value = 20 },
         { FabricIndex = B, Value = 30 },
         { FabricIndex = A, Value = 40 },
         { FabricIndex = B, Value = 55 },
         { FabricIndex = B, Value = 60 } ]
```

7.19.1.9. Struct Type

A struct is a sequence of fields of any data type. Individual fields are identified by a field ID of unsigned integer, starting at 0 (zero), for the first field.