

Class	Data Type	Short	Base Type	Size
Composite	String			
	Character String	string	octstr	desc
	Address			
	IP Address	ipadr	octstr	4 or 16 bytes
	IPv4 Address	ipv4adr	octstr	4 bytes
	IPv6 Address	ipv6adr	octstr	16 bytes
	IPv6 Prefix	ipv6pre	octstr	1 to 17 bytes
	Hardware Address	hwadr	octstr	6 or 8 bytes
	Tag			
	Semantic Tag	semtag	struct	4 bytes
	Location			
	Location Descriptor	locationdesc	struct	variable
	Financial			
	Currency	currency	struct	variable
	Price	price	struct	variable

7.19.2.1. Percentage Type

A Percentage is an unsigned 8-bit value representing percent with a resolution of 1%. The range is from 0 (0%) to 100 (100%).

7.19.2.2. Percentage100ths Type

A Percentage 100ths is an unsigned 16-bit value representing percent with a resolution of 0.01%. The range is from 0 (0.00%) to 10000 (100.00%).

7.19.2.3. Epoch Time in Microseconds Type

This type represents an offset, in microseconds, from 0 hours, 0 minutes, 0 seconds, on the 1st of January, 2000 UTC (the Epoch), encoded as an unsigned 64-bit scalar value.

This offset is the sum of two parts: time elapsed, not counting leap-seconds, and a local time offset. The local time offset MAY include a timezone offset and a MAY include a DST offset.

Any use of this type SHALL indicate how the associated local time offset is determined in the specific context of that use. This MAY be done, for example, by simply saying the time is a UTC time, in which case the local time offset is 0.

A given Epoch Time value MAY be interpreted in at least two ways:

1. The value can be converted to a local clock date/time (year, month, day, hours, minutes, sec-