

7.19.2.14. Apparent Power Type

This type, derived from int64, represents apparent power measured in millivolt-amps.

7.19.2.15. Apparent Energy Type

This type, derived from int64, represents apparent energy measured in millivolt-amp-hours.

7.19.2.16. Reactive Power Type

This type, derived from int64, represents reactive power measured in millivolt-amps reactive.

7.19.2.17. Reactive Energy Type

This type, derived from int64, represents reactive energy measured in millivolt-amp-hours reactive.

7.19.2.18. Money Type

This type, derived from int64, represents an amount of money.

The money type SHALL be used in concert with a [CurrencyStruct](#) to indicate the currency in use, as well as the number of digits after the decimal point in the amount of that currency.

For example, if a given money value is 1015, the value of the associated [Currency](#) field is 840 (USD), and the value of the associated [DecimalPoints](#) field is 4, then the represented amount would be 0.1015 dollars, or 10.15 cents.

Similarly, if a given money value is 1015, the value of the associated [Currency](#) field is 978 (EUR), and the value of the associated [DecimalPoints](#) field is 2, then the represented amount would be 10.15 euros.

Similarly, if a given money value is 1015, the value of the associated [Currency](#) field is 392 (JPY), and the value of the associated [DecimalPoints](#) field is 0, then the represented amount would be 1015 yen.

Operations involving money types SHALL be done using fixed point arithmetic. The results of arithmetic operations involving money SHALL be rescaled in accordance with the associated [Currency](#) structure rather than result in altering the [DecimalPoints](#).

7.19.2.19. Enumeration Type (8-bit, 16-bit)

This data type employs scalars to represent context-specific values available from an enumerated set. This data type is nullable.

A data field of this type SHALL have well-defined values with well-defined conformance for implementation. A base cluster that requires derivation MAY defer the definition of all or some enumerated values to the derivation that can be implemented. Such a base cluster MAY also define constraints, such as ranges and semantics of those ranges for the enumeration.

Values for an enumeration MAY be defined directly in a cluster specification, in a derived cluster specification, or in a separate namespace defined in the cluster specification. For examples, please