

- the [accessing fabric index](#) of an interaction
- the [FabricIndex global field](#) in [fabric-scoped data](#)

7.19.2.24. Node ID Type

A [64-bit ID for a node](#) scoped and unique to a particular fabric as indicated by an accompanying [fabric-index](#) adjacent instantiation.

7.19.2.25. Subject ID Type

A [64-bit integer](#) that identifies the source of an action, referencing an entity that is authenticated via a method provided by the secure channel architecture.

Any use of a Subject ID needs to be accompanied by a method to determine which type of subject is being represented. There are several types of subjects that may need to be disambiguated, depending on the authentication mode used:

- PASE: Lower 16 bits represent the Passcode ID, upper 48 bits are clear.
- CASE: 64 bits represent either the Node ID or a CASE Authenticated Tag.
- Group: Lower 16 bits represent the Group ID, upper 48 bits are clear.

7.19.2.26. Group ID Type

A [16-bit ID for a group](#) scoped to a particular fabric as indicated by an accompanying [fabric index](#) adjacent instantiation.

7.19.2.27. Endpoint Number Type

An unsigned number that indicates an instance of a [device type](#). Endpoint numbers SHALL NOT be 0xFFFF, to allow all endpoint number values to be expressible in nullable endpoint-no fields.

7.19.2.28. Vendor ID Type

A [Vendor ID](#).

Vendor IDs MAY be used as a prefix in a [Manufacturer Extensible Identifier](#) format.

7.19.2.29. Device Type ID Type

An identifier that indicates conformance to a [device type](#).

Device Type IDs SHALL be a [Manufacturer Extensible Identifier](#). The specifics of its representation are described in [Data Model Types](#).

7.19.2.30. Cluster ID Type

An identifier that indicates conformance to a cluster specification.

Cluster IDs SHALL be a [Manufacturer Extensible Identifier](#). The specifics of its representation are described in [Data Model Types](#).