

7.19.2.31. Attribute ID Type

An identifier that indicates an attribute defined in a cluster specification.

Attribute IDs SHALL be a [Manufacturer Extensible Identifier](#). The specifics of its representation are described in [Data Model Types](#).

7.19.2.32. Field ID Type

An identifier that indicates a field defined in a struct.

Field IDs SHALL be a [Manufacturer Extensible Identifier](#). The specifics of its representation are described in [Data Model Types](#).

7.19.2.33. Event ID Type

An identifier that indicates an [Event](#) defined in a cluster specification.

Event IDs SHALL be a [Manufacturer Extensible Identifier](#). The specifics of its representation are described in [Data Model Types](#).

7.19.2.34. Command ID Type

An identifier that indicates a [command](#) defined in a cluster specification.

Command IDs SHALL be a [Manufacturer Extensible Identifier](#). The specifics of its representation are described in [Data Model Types](#).

7.19.2.35. Action ID Type

An identifier that indicates an action as defined in the [Interaction Model](#) specification.

7.19.2.36. Transaction ID Type

An identifier for a transaction as defined in the [Interaction Model](#) specification, see [Transaction ID](#).

7.19.2.37. Entry Index Type

This is an index for a [list data type](#).

7.19.2.38. Data Version Type

An unsigned number that indicates a [Data Version](#).

7.19.2.39. Event Number Type

An unsigned number that indicates an [Event](#) instance.

7.19.2.40. Character String Type

The character string data type is derived from an octet string. The octets SHALL be characters with UTF-8 encoding. An instance of this data type SHALL NOT contain truncated code points.