

Tag Field

The Tag field SHALL be the ID of a semantic tag located within the namespace indicated by NamespaceID.

A device MAY expose tags from the common or device-specific namespaces and from manufacturer-specific namespaces in a single [Section 9.5.6.5, “TagList”](#).

Label Field

The Label field, if present, SHALL contain human-readable text suitable for display on a client. The content of the Label field is defined by the manufacturer.

This field SHALL be present when the MfgCode is not NULL. This field SHOULD NOT be used if the Tag is from a standard namespace, unless the Tag requires further qualification. For example: A Tag that has the meaning of "room" in a location namespace, would require the a label string to qualify the type of room, such as "1", "2b", "Bathroom", etc.

7.19.2.47. Namespace Type

The Namespace type identifies the namespace used for a semantic tag.

7.19.2.48. Tag Type

The Tag type SHALL identify a semantic tag located within a namespace.

7.19.2.49. LocationDescriptorStruct Type

This data type SHALL be represented by the following structure:

ID	Name	Type	Constraint	Quality	Fallback	Access	Conformance
0	Location-Name	string	max 128				M
1	Floor-Number	int16		X			M
2	AreaType	tag		X			M

LocationName Field

This field SHALL indicate the name of the location. For example, "blue room".

If the location name is not user provided, the logic that generates it (clients, devices etc.) SHOULD utilize synthesized user-friendly, understandable, names for the location, rather than opaque values such as "private" or "2fe7c241-a50a-4863-896e-c5878da5ed68".

FloorNumber Field

This field SHALL indicate the level number. Negative values correspond to basement levels.