

| Prefix            | Source                                                                                              |
|-------------------|-----------------------------------------------------------------------------------------------------|
| 0x0000            | Standard OR Scoped                                                                                  |
| 0x0001 - 0xFFFF0  | Manufacturer Code as per <a href="#">Connectivity Standards Alliance Manufacturer Code Database</a> |
| 0xFFFF1 - 0xFFFF4 | Test Vendor MC                                                                                      |

The MEI suffix encodes a key as follows:

Table 99. MEI Suffix

| Suffix           | Item            |
|------------------|-----------------|
| 0x0000 - 0xFFFFE | Item 0 to 65534 |

### 7.21.2.2. Data Model Types

The following data model types SHALL be represented as MEIs:

Table 100. MEI Suffix

| Type                      | Permitted Source Types | Suffix Range                                    |
|---------------------------|------------------------|-------------------------------------------------|
| Device Type ID            | Standard or MC         | 0x0000 - 0xBFFF                                 |
| Cluster ID                | Standard or MC         | Standard Cluster: 0x0000 - 0x7FFF               |
|                           |                        | Manufacturer-Specific Cluster: 0xFC00 - 0xFFFFE |
| Attribute ID (Global)     | Standard               | 0xF000 - 0xFFFFE                                |
| Attribute ID (Non-Global) | Scoped or MC           | 0x0000 - 0x4FFF                                 |
| Event ID                  | Scoped or MC           | 0x00 - 0xFF                                     |
| Command ID (Global)       | Standard               | 0xE0 - 0xFF                                     |
| Command ID (Non-Global)   | Scoped                 | 0x00 - 0xDF                                     |
| Command ID                | MC                     | 0x00 - 0xFF                                     |
| Field ID (Global)         | Standard               | 0xE0 - 0xFE                                     |
| Field ID (Non-Global)     | Scoped or MC           | 0x00 - 0xDF                                     |

For those types which are listed with an 8 bit suffix range in this table (i.e. Event ID, Command ID and Field ID), the 16-bit MEI Suffix SHALL be constructed by padding the 8-bit data with a most significant byte set to zero.

For example:

Table 101. MEI Decoding Example

| MEI         | Description            |
|-------------|------------------------|
| 0x0000_0000 | Standard/Scoped item 0 |