

Endpoint	Cluster	Attribute	Attribute Description	Struct Field	Field Description
0x0001	0x000C_FC01 ³	0x0000_0001 ³	Sensor 1 Stats ³	0x0000_0001 ³	Value ³
				0x0000_0002 ³	Precision ³
				0x0000_0003 ³	Accuracy ³
		0x0000_0002 ³	Counter 1 (period = hour) ³	0x0000_0001 ³	Min daily count ³
				0x0000_0002 ³	Max daily count ³
				0x0000_0003 ³	Mean daily count ³

Note the following potential combinations of path components:

Table 106. Hypothetical Manufacturer Extension Path Examples

	Description
0x0001/0x0000_ABCD/0x0000_0003/0x0000_0001	Cluster ID = Standard, Attribute ID = Scoped, Field ID = Scoped: Counter 1 min value
0x0001/0x0000_ABCD/0x0000_0003/0x000A_0001	Cluster ID = Standard, Attribute ID = Scoped, Field ID = MS(A): Counter 1 Q1 daily count over last month
0x0001/0x0000_ABCD/0x000B_0001/0x0000_0001	Cluster ID = Standard, Attribute ID = MS(B), Field ID = Scoped: Counter 1 Q1 daily count over last year
0x0001/0x0000_ABCD/0x000B_0001/0x000A_0001	Cluster ID = Standard, Attribute ID = MS(B), Field ID = MS(A): Counter 1 Q1 daily count over last year
0x0001/0x000C_FC01/0x0000_0001/0x0000_0002	Cluster ID = MS(C), Attribute ID = Scoped, Field ID = Scoped: Sensor 1 precision
0x0001/0x000C_FC01/0x0000_0002/0x0000_0003	Cluster ID = MS(C), Attribute ID = Scoped, Field ID = Scoped: Counter 1 (period = hour) Mean
0x0001/0x000C_FC01/0x0000_FFFD	Cluster ID = MS(C), Attribute ID = Standard: Cluster revision

7.21.4. Discoverability

The Descriptor Cluster reports the device types and clusters on a node's endpoints, whether they are standard or from a particular manufacturer.

For example, if a node supports cluster 0x000C_ABCD on endpoints 1 and 2, that information is available in the Descriptor Cluster.