

```

<target> ::= <group target> | <endpoint target>
<group target> ::= <group ID>
<endpoint target> ::= <node> <endpoint>
<endpoint> ::= <wildcard endpoint> | <concrete endpoint>
<cluster> ::= <wildcard cluster> | <concrete cluster>
<cluster element> ::= <attribute> | <event> | <command>

```

An [Attribute Path](#) is a path indicating an [attribute](#).

A [Command Path](#) is a path indicating a [command](#).

An [Event Path](#) is a path indicating an [event](#).

8.2.1.1. Concrete Path

- A concrete path SHALL NOT have group IDs or wildcards.
- A concrete path SHALL indicate a single element instance that is either:
 - an event with the path ending in an event ID
 - a command with the path ending in a command ID
 - an attribute with the path ending in an attribute ID
 - a struct field with the path ending in a field ID
 - a list entry with the path ending in a list entry index.

8.2.1.2. Existent Path

- An existent path is a concrete path that indicates a single existing instance on the node indicated in the path.

8.2.1.3. Group Path

A group path is a path that targets endpoints that are members of a group, using group ID, instead of indicating a node and endpoint.

- A group path SHALL resolve into zero or more paths.
- A group path SHALL include a group ID that indicates zero or more endpoints that are members of the group.
- A group path MAY include a wildcard cluster indication and therefore also be a [Wildcard Path](#).

8.2.1.4. Wildcard Path

A wildcard path is a path with a wildcard endpoint indication and/or wildcard cluster indication.

- A wildcard path SHALL resolve into zero or more paths.
- A wildcard path SHALL indicate zero or more element instances.
- A wildcard path MAY include a group ID and therefore also be a [Group Path](#).