

<nesting level> ::= <struct field ID> | <list entry index>

* <nesting level> occurs zero or more times as defined in a cluster specification.

The endpoint component is subject to wildcard expansion, as constrained in particular actions and contexts.

Attribute Wildcard Path Flags

Processing wildcard expansion of an Attribute Path MAY be affected by the associated WildcardPathFlags and WildcardFilterConfigurationVersion fields.

When expanding a wildcard path indicated in an [AttributePathIB](#) into one or more concrete paths, paths SHALL be omitted from the result set if the [WildcardFilterConfigurationVersion](#) is greater than or equal to the current [ConfigurationVersion Attribute](#) in the Basic Information cluster and they satisfy any of the conditions below, each of which depends on the value of [WildcardPathFlags](#) and the path being considered:

- if the [WildcardSkipRootNode](#) bit is set and the concrete path targets endpoint 0;
- if the [WildcardSkipGlobalAttributes](#) bit is set and the concrete path refers to one of the following attribute IDs:
 - GeneratedCommandList/0xFFFF8
 - AcceptedCommandList/0xFFFF9
 - AttributeList/0xFFFFB
- if the [WildcardSkipAttributeList](#) bit is set and the concrete path refers to the AttributeList (ID 0xFFFFB) attribute;
- if the [WildcardSkipCommandLists](#) bit is set and the concrete path refers to the either the GeneratedCommandList (ID 0xFFFF8) or AcceptedCommandList (ID 0xFFFF9) attributes;
- if the [WildcardSkipCustomElements](#) bit is set, and the concrete path targets:
 - any element whose Cluster ID has an [MEI prefix](#) not equal to zero;
 - any attribute whose ID has an [MEI prefix](#) not equal to zero, even if included in a standard cluster;
- if the [WildcardSkipFixedAttributes](#) bit is set and the concrete path refers to an attribute with the Fixed (F) quality;
- if the [WildcardSkipChangesOmittedAttributes](#) bit is set and the concrete path refers to an attribute with the Changes Omitted (C) quality;
- if the [WildcardSkipDiagnosticsClusters](#) bit is set and the concrete path refers to a cluster with the [Diagnostics \(K\) quality](#).

WildcardPathFlags SHALL ONLY be used for either Read or Subscribe interactions.

If the client is including WildcardPathFlags in an AttributePathIB destined to a server that pre-dates the introduction of WildcardPathFlags (currently provisional), the client SHALL tolerate the inclusion of reports for paths that would otherwise be omitted by servers compliant with this feature.