

NOTE

Support for WildcardPathFlags and WildcardFilterConfigurationVersion is provisional.

8.2.1.8. Command Path

A command path is used to indicate a cluster command.

Associated Information Block: [CommandPathIB](#)

- The **<command>** component of a command path SHALL have the following form:

```
<command> ::= <command ID>
```

- The endpoint field is wildcardable, though this may be disallowed in the various uses of the Command Path in different actions and contexts.

8.2.1.9. Event Path

A event path is used to indicate a cluster event.

Associated Information Block: [EventPathIB](#)

- The **<event>** component of an event path SHALL have the following form:

```
<event> ::= <event ID>
```

See [Section 7.14, “Event”](#) for a description of a cluster event and event data fields.

The endpoint, cluster and event ID fields are wildcardable. These are further constrained in the various uses of the Event Path in different actions and contexts.

- An event path SHALL NOT be a group path.

8.2.2. Interaction

An interaction is a sequence of one or more transactions between nodes, that occurs in the context of an [accessing fabric](#), or no fabric.

How a fabric, or no fabric, context is established for an interaction, is not defined here.

The first transaction (of an interaction) starts with the first action from the node called the **initiator**. The first action destination is called the **target**, which is either a node or group. For the remainder of the interaction, the initiator remains the same.

An interaction may be a single transaction (e.g. Read). An interaction may be an unbounded number of transactions (e.g. Subscribe).