

Interaction	Transactions	Description
Read Interaction	Read	This interaction is a request for cluster attributes and/or event data.
Subscribe Interaction	Subscribe, Report	This interaction subscribes to cluster attributes and/or event data.
Write Interaction	Write	This interaction modifies cluster attributes.
Invoke Interaction	Invoke	This interaction invokes cluster commands.

8.2.3. Transaction

A transaction is either the whole, or part of an interaction. A transaction is a sequence of one or more actions. Actions in a transaction are defined as first or following, to better describe dependencies in this specification.

- The first action of a transaction SHALL be initiated by a single node.
- An action in a transaction SHALL have a target destination that is either a single node, called a unicast action or a group of nodes, called groupcast action.

8.2.3.1. Transaction ID

The transaction ID is a field present in all actions (see [Common Action Information](#)) that indicates the logical grouping of those actions.

- All following actions in a transaction SHALL have the same transaction ID as the first action.
- A groupcast action SHALL end a transaction and any subsequent action in the interaction SHALL NOT use the same transaction ID.

The table below lists all transactions.

Transaction	Description
Read Transaction	This transaction is a request for cluster attribute and/or event data.
Subscribe Transaction	This transaction creates a subscription to cluster attributes and/or events.
Report Transaction	This transaction maintains a subscription for the Subscribe interaction.
Write Transaction	This transaction modifies cluster attributes.
Invoke Transaction	This transaction invokes cluster commands.