

8.2.4. Action

The table below lists all actions.

Action	Description	Outgoing Message
Status Response Action	This action is a success or error response.	Unicast
Read Request Action	This action is a request for cluster attribute data and/or events.	Unicast
Report Data Action	This action responds to a Read Request Action or Subscribe Request Action .	Unicast
Subscribe Request Action	This action is a request for a subscription to cluster attribute data and/or events.	Unicast
Subscribe Response Action	This action is a response to a Subscribe Request Action .	Unicast
Write Request Action	This action is a request to modify cluster attribute data.	Unicast Groupcast
Write Response Action	This action responds to a Write Request Action .	Unicast
Invoke Request Action	This action executes a cluster command.	Unicast Groupcast
Invoke Response Action	This action is used to respond to an Invoke Request Action with cluster defined responses.	Unicast
Timed Request Action	This action indicates that another action will take place within a Timed interval.	Unicast

8.2.5. Common Action Behavior

The message layer below this interaction layer encodes an action into one or more messages and delivers the messages to a destination. This interaction layer delivers action information to the message layer by passing action information, through some interface (not defined here). The message layer delivers action information, from an incoming message, to this interaction layer.

In all action descriptions in this specification, action information (or information blocks), refers to the information that is transferred to and from the message layer.

There is no designation of mandatory or optional for such information because the implementation is undefined. However, some information fields may be omitted, meaning the information may not be needed for all actions.