

8.2.5.1. Common Action Information

Action Field	Type	Conformance	Description
InteractionModelRevision	uint8	M	the revision number of the implemented Interaction Model specification under which the sending node was certified
Action	action-id	M	the action
TransactionID	trans-id	M	the transaction ID
FabricIndex	fabric-idx	M	the accessing fabric index , based on the session used to deliver the action
SourceNode	node-id	M	the node ID of the node that generates the action
DestinationNode	node-id	O.a	the node ID of the destination where the action is sent
DestinationGroup	group-id	O.a	the group ID of the destination where the action is sent
<i>action specific</i>	<i>variable</i>	M	specific action information described in each action section

8.2.5.2. Outgoing Action

- Each generated action SHALL provide the action information above to the message layer.
- If the action is the first action of a transaction, the TransactionID SHALL be a value that uniquely identifies the transaction on the source of the action.
- If the action is a following action, the TransactionID SHALL be the same as the TransactionID in the first action of the transaction.
- If the action is a unicast following action the DestinationNode SHALL be the SourceNode of the previous action in the transaction.
- The generated action information SHALL be submitted to the message layer.
 - Upon receipt of this action information, the message layer SHALL construct and convey one or more messages for this action to the target.
 - If the message layer encounters an error that prevents the complete construction, encoding and/or conveyance of the action, then the message layer SHALL inform this layer of the error.