

- If the action is not completely conveyed, the action, with the associated transaction and interaction, SHALL terminate.
 - If the failed action is NOT a Status Response action, this layer SHOULD, if possible, submit a Status Response action to the message layer, with a status code of FAILURE and the same TransactionID.

8.2.5.3. Incoming Action

- If the message layer receives a valid message for an action, it SHALL be delivered to this layer with the action information above.
- If this layer receives a message for an action that is not expected semantically, has invalid action information, or has an error not described in this specification, a Status Response action with an INVALID_ACTION Status Code SHALL be generated as defined in [Status Response Action](#), and the associated transaction and interaction SHALL terminate.
- If during the receipt and decoding of messages for an action by the message layer, an error occurs that prevents a complete receipt of a valid action, then the message layer SHALL inform this layer of the error.
 - When informed of an error from a message layer, the action, with the associated transaction and interaction, SHALL terminate.
- If the action is not able to be executed due to insufficient resources, a Status Response SHALL be sent to the initiator with a status code of either:
 - PATHS_EXHAUSTED if there are not enough resources to support the number of paths in the action information,
 - and the number of paths in the action exceeds the number of paths that is guaranteed to be supported for the action (see [Interaction Model Limits](#)),
 - BUSY in all other recoverable resource exhausted situations (e.g. if too many Read interactions are already in progress),
 - or RESOURCE_EXHAUSTED for any other resource insufficiency,
 - and the interaction SHALL be terminated.

It is implementation specific whether the message layer submits logical parts of an action to this layer as it receives and processes each message. The only requirement above is that all the information, or an error, be submitted to this layer.

Global common interaction Status Codes are defined in this document in [Status Codes](#). Cluster specific Status Codes are defined in each cluster specification.

8.3. Status and Interaction

There is no Status interaction, but an error status may be generated as part of any interaction.

8.3.1. Status Response Action

This action is defined as a following action for some actions, or is generated when there is an