

8.4.1. Read Transaction

Action	Action Flow	Description
Read Request	Initiator ⇒ Target	data report request
Report Data	Initiator ⇐ Target	response report with data

8.4.2. Read Request Action

Read Request action is the first action of a Read transaction (and interaction). See [Section 8.2.5, “Common Action Behavior”](#) for behavior common to all actions. The specific action information for this action is shown below.

8.4.2.1. Read Request Action Information

Action Field	Type	Conformance	Description
AttributeRequests	list[AttributePathIB]	M	a list of zero or more request paths to cluster attribute data
DataVersionFilters	list[DataVersionFilterIB]	AttributeRequests	a list of zero or more cluster instance data versions
EventRequests	list[EventPathIB]	M	a list of zero or more request paths to cluster events
EventFilters	list[EventFilterIB]	EventRequests	a list of zero or more minimum event numbers per specific node
FabricFiltered	bool	M	limits the data read within fabric-scoped lists to the accessing fabric

8.4.2.2. Outgoing Read Request Action

- This action SHALL be unicast.
- This action SHALL be generated as the first action in a Read transaction.
- A valid [AttributePathIB](#) for attribute data SHALL be one in the table [Valid Read Attribute Paths](#).
- A valid [EventPathIB](#) for an event SHALL be one in the table [Valid Event Paths](#).
- A path indicated in AttributeRequests or EventRequests SHALL NOT target a group.

8.4.2.3. Incoming Read Request Action

- Upon receipt of this action, this layer SHALL generate a Report Data action to the subscriber, as defined in [Incoming Read Request and Subscribe Request Action Processing](#).