

- If the Report Data was generated successfully, it SHALL be submitted to the message layer.

8.4.3. Report Data Action

This action is either a first action in a Report transaction (as part of a Subscribe interaction), or a following action to a Read Request action or Subscribe Request action.

See [Section 8.2.5, “Common Action Behavior”](#) for behavior common to all actions. The specific action information for this action is shown below.

8.4.3.1. Report Data Action Information

Action Field	Type	Conformance	Description
SuppressResponse	bool	M	do not send a response to this action
SubscriptionId	uint32	O	a SubscriptionId only used in a Subscribe interaction
AttributeReports	list[AttributeReportIB]	O	a list of zero or more attribute data reports
EventReports	list[EventReportIB]	O	a list of zero or more event reports

8.4.3.2. Incoming Read Request and Subscribe Request Action Processing

- Each path indicated by the Report Data action SHALL be a [Concrete Path](#).
- Upon receipt of a Read Request action or Subscribe Request action, this process SHALL be followed:
- Each request path in the AttributeRequests field SHALL be processed as follows:
 - If the path does not conform to [Valid Read Attribute Paths](#) then:
 - a Status Response with the INVALID_ACTION Status Code SHALL be generated as defined in [Status Response Action](#), a Report Data action SHALL NOT be generated, and this interaction and process SHALL terminate.
 - Else if the path is a concrete path, the path SHALL be processed as follows, terminating further processing of the concrete path immediately if a failure [AttributeStatusIB](#) is generated at any point.
 - Execute the [ACL Access Granting Algorithm](#) against the concrete path, assuming the **required_privilege** for the element is View, to determine whether the subject would have had at least some access against the concrete path.
 - If the outcome is AccessDenied, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
 - Else if the outcome is AccessRestricted, an [AttributeStatusIB](#) SHALL be generated with the ACCESS_RESTRICTED Status Code.