

- Otherwise, continue processing.
- Determine element existence from the concrete path, and apply the following checks:
 - If the path indicates a node that is unsupported, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_NODE Status Code.
 - Else if the path indicates an endpoint that is unsupported, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_ENDPOINT Status Code.
 - Else if the path indicates a cluster that is unsupported, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_CLUSTER Status Code.
 - Else if the path indicates an attribute or attribute data field that is unsupported, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_ATTRIBUTE Status Code with the Path field indicating the first unsupported data field (not the entire attribute data path).
 - Else if the path indicates an attribute that is not readable, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_READ Status Code.
- Execute the [ACL Access Granting Algorithm](#) against the concrete path a second time, using the actual [required_privilege](#) for the attribute referenced in the path.
 - If the outcome is AccessDenied, an [AttributeStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
 - Else if the outcome is AccessRestricted, an [AttributeStatusIB](#) SHALL be generated with the ACCESS_RESTRICTED Status Code.
 - Otherwise, continue processing.
- If an [AttributeStatusIB](#) was generated, the path SHALL be discarded.
- Else perform [Request Path Expansion](#) and process each expanded existent path as follows:
 - If the path indicates attribute data that is not readable, then the path SHALL be discarded.
 - Execute the [ACL Access Granting Algorithm](#) against the path, using the actual [required_privilege](#) for the attribute referenced in the path.
 - If the outcome is either AccessDenied or AccessRestricted, then the path SHALL be discarded.
 - Otherwise, continue processing.
- If no error-free existent paths remain, then AttributeRequests are considered empty.
- Else each remaining error-free existent path is processed as follows:
 - If the DataVersionFilters field indicates [DataVersionFilterIB](#) entries with a Path field that matches the path, where all matching entries have a DataVersion field that matches the data version of the cluster instance in the path, then the path SHALL be ignored
 - Else an [AttributeDataIB](#) SHALL be generated with the Data and Path as indicated by the path being processed. If the attribute indicated by the path or any struct field nested inside that attribute (at any level of nesting) is a fabric-scoped list, then any such list within the generated Data SHALL be processed as follows:
 - If the FabricFiltered parameter is true, or the attribute indicated by the path is [fabric-](#)