

[sensitive](#), any such list SHALL be generated as a [fabric-filtered list](#) of entries.

- Else, any such list SHALL be generated as an unfiltered list of entries, with each entry indicated as a [fabric-sensitive struct](#).
- Each [AttributeDataIB](#) or [AttributeStatusIB](#) generated from processing [AttributeRequests](#) SHALL be added to the [AttributeReports](#) action field in the Report Data action.
- Each request path in the [EventRequests](#) field SHALL be processed as follows:
 - If the path is a concrete path, the path SHALL be processed as follows, terminating further processing of the concrete path immediately if a failure [EventStatusIB](#) is generated at any point.
 - Execute the [ACL Access Granting Algorithm](#) against the concrete path, assuming the [required_privilege](#) for the element is View, to determine whether the subject would have had at least some access against the concrete path.
 - If the outcome is AccessDenied, an [EventStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
 - Else if the outcome is AccessRestricted, an [EventStatusIB](#) SHALL be generated with the ACCESS_RESTRICTED Status Code.
 - Otherwise, continue processing.
 - Determine element existence from the concrete path, and apply the following checks:
 - If the path indicates a node that is unsupported, an [EventStatusIB](#) SHALL be generated with the UNSUPPORTED_NODE Status Code.
 - Else if the path indicates an endpoint that is unsupported, an [EventStatusIB](#) SHALL be generated with the UNSUPPORTED_ENDPOINT Status Code.
 - Else if the path indicates a cluster that is unsupported, an [EventStatusIB](#) SHALL be generated with the UNSUPPORTED_CLUSTER Status Code.
 - Else if the path indicates a cluster event that is unsupported, an [EventStatusIB](#) SHALL be generated with the UNSUPPORTED_EVENT Status Code.
 - Execute the [ACL Access Granting Algorithm](#) against the concrete path a second time, using the actual [required_privilege](#) for the event referenced in the path.
 - If the outcome is AccessDenied, an [EventStatusIB](#) SHALL be generated with the UNSUPPORTED_ACCESS Status Code.
 - Else if the outcome is AccessRestricted, an [EventStatusIB](#) SHALL be generated with the ACCESS_RESTRICTED Status Code.
 - Otherwise, continue processing.
 - If an [EventStatusIB](#) was generated, the path SHALL be discarded.
 - Else if the path does not conform to [Valid Event Paths](#) then:
 - a Status Response with the INVALID_ACTION Status Code SHALL be generated as defined in [Status Response Action](#),
 - a Report Data action SHALL NOT be generated,
 - and this interaction and process SHALL terminate.