

- Else perform [Request Path Expansion](#) and process each expanded existent path as follows:
 - Execute the [ACL Access Granting Algorithm](#) against the path, using the actual [required_privilege](#) for the event referenced in the path.
 - If the outcome is either AccessDenied or AccessRestricted, then the path SHALL be discarded.
 - Otherwise, continue processing.
- If no error free existent paths remain, then EventRequests are considered empty.
- Else for each unique node indicated in the remaining existent paths:
 - Each event record currently queued in the node, in order from lowest to highest event number, SHALL generate an [EventDataIB](#) except for any of the following:
 - If the node indicated matches the Node information field of an [EventFilterIB](#) from Event-Filters, and the event number is less than the EventMin field in the [EventFilterIB](#).
 - If the event record path does not match a path in the remaining existent event paths.
 - If the event record path is [fabric-sensitive](#), and the [associated fabric](#) does not match the [accessing fabric](#).
 - Each information block generated from processing EventRequests SHALL be added to the EventReports action field in the Report Data action.
- If this action is a Subscribe Request action,
 - If both AttributeRequests and EventRequests are empty
 - a [Status Response Action](#) with the INVALID_ACTION Status Code SHALL be sent to the initiator,
 - a Report Data action SHALL NOT be generated,
 - and the interaction and process SHALL terminate.
 - Else if either MinIntervalFloor or MaxIntervalCeiling is missing, or MinIntervalFloor is greater than MaxIntervalCeiling
 - a [Status Response Action](#) with the INVALID_ACTION Status Code SHALL be sent to the initiator,
 - a Report Data action SHALL NOT be generated,
 - and the interaction and process SHALL terminate.
 - Else a SubscriptionId which uniquely identifies this subscription on the publisher SHALL be indicated in the Report Data action
- Else the SubscriptionId SHALL be omitted.

8.4.3.3. Outgoing Report Data Action

- This action SHALL be unicast.
- This action MAY have an empty list of AttributeReports and/or EventReports.
- This action SHALL NOT include any nested attribute data field or nested event data field that is defined as fabric-sensitive, if the [associated fabric](#) for that field does not match the [accessing](#)