

requested in the [Subscribe transaction](#) are the subscription data.

This interaction starts by creating a subscription with a [Subscribe transaction](#), which primes the subscriber with initial subscription data. The rest of the subscription is a sequence of [Report transactions](#) initiated by the publisher as defined by parameters of the subscription. Each [Report transaction](#) in a subscription reports changes to the subscription data.

To keep the subscription alive, a [Report transaction](#) is sent from the publisher every maximum interval, or possibly more frequently.

[Report transactions](#) from the publisher are rate limited by the minimum interval subscription parameter, as negotiated between the subscriber and publisher.

The [Subscribe Request](#) action provides boundary values (floor or ceiling) for the publisher to determine the final minimum and maximum interval parameters of the subscription. The time units for these intervals are seconds.

Each [Subscribe](#) interaction is a subscription that is identified by a Subscription ID as generated by the publisher.

- The [Subscribe](#) interaction SHALL start with one [Subscribe transaction](#) followed by a periodic sequence of [Report transactions](#) (see [Report Transaction](#)).
- A [Report transaction](#) SHALL be initiated by a [Report Data](#) action as part of an active subscription for a [Subscribe](#) interaction.
- All [Report Data](#) actions in a [Subscribe](#) interaction SHALL have the same [SubscriptionId](#) parameter value that uniquely identifies the interaction among all subscriptions on the publisher.
- Each [Report transaction](#) in a subscription SHALL report the path for each delta change in the subscription data, including the attribute data that has changed and/or the event that has occurred, since the last [Report transaction](#), with the exception of attribute data with the [Changes Omitted \(C\) quality](#).
- Each [Report transaction](#) initiated by the publisher SHALL complete successfully before another [Report transaction](#) is initiated by the publisher.
- Each [Report transaction](#) SHALL NOT be initiated by the publisher until the minimum interval has expired since the last [Report transaction](#) in the subscription.
- Attribute changes SHALL be delivered as soon as possible, taking into account the minimum interval.
- Events SHALL always be queued and buffered. Each [Report](#) containing events SHALL deliver queued events without reordering the queue. Queued events MAY be opportunistically delivered whenever some other activity triggers a [Report transaction](#). Absent any such triggers, queued events SHALL be delivered in a [Report transaction](#) generated at the maximum interval.
- When the [IsUrgent](#) flag is FALSE or absent for a subscription's event path in the [EventPathIB](#), event queueing does not automatically trigger a [Report transaction](#).
- When the [IsUrgent](#) flag is TRUE for a subscription's event path in the [EventPathIB](#), the queueing of such an event SHALL trigger a [Report transaction](#) for the subscription, subject to all [Report transaction](#) rules. This [Report transaction](#) will report the events that have been queued by the time the [Report transaction](#) happens.