

8.7. Write Interaction

This interaction is started when an initiator wishes to modify the values of one or more attributes located on one or more nodes. An optional Timed Request action defines a Timeout interval that starts at the sending of the Status Response action.

8.7.1. Write Transaction

- A Write interaction SHALL consist of one of the transactions shown below.

8.7.1.1. Timed Write Transaction

Action	Action Flow	Description
Timed Request	Initiator $\Rightarrow$ Target	time interval defined to send Write Request action
Status Response	Initiator $\Leftarrow$ Target	confirmation
Write Request	Initiator $\Rightarrow$ Target	data to modify
Write Response	Initiator $\Leftarrow$ Target	with errors or success from Write Request action

8.7.1.2. Untimed Write Transaction

Action	Action Flow	Description
Write Request	Initiator $\Rightarrow$ Target	data to modify
Write Response	Initiator $\Leftarrow$ Target	with errors or success from Write Request action

- If there is a preceding successful Timed Request action, the following Write Request action SHALL be received before the end of the Timeout interval.
- If there is a preceding successful Timed Request action, the Timeout interval SHALL start when the Status Response action acknowledging the Timed Request action with a success code is sent.
- If there is a preceding successful Timed Request action, the Write Request action SHALL be unicast.
- If there is not a preceding successful Timed Request action, the Write Request action MAY be groupcast.
- A client MAY choose to use a Timed Write transaction even if the attribute does not have the Timed Interaction quality.
- The server SHALL support a Timed Write transaction for all writeable attributes.

8.7.2. Write Request Action

This action is either the first action of the Write transaction or it follows a successful Timed Request action. See [Section 8.2.5, “Common Action Behavior”](#) for behavior common to all actions. The specific action information for this action is shown below.