

8.7.2.1. Write Request Action Information

Action Field	Type	Conformance	Description
SuppressResponse	bool	M	do not send a response to this action
TimedRequest	bool	M	flag action as part of a timed write transaction
WriteRequests	list[AttributeDataIB]	M	a list of one or more path and data tuples.

8.7.2.2. Outgoing Write Request Action

- This action SHALL be generated as the first action in a Write transaction, or following a Timed Request action and successful Status Response action.
- If this action is part of a Timed Write transaction, TimedRequest SHALL be TRUE, else FALSE.
- If not part of a Timed Write transaction, this action MAY be groupcast.
- If this action is groupcast, SuppressResponse SHALL be TRUE.

8.7.2.3. Incoming Write Request Action

- If this action is not able to be executed because the maximum supported number of Write interactions is already in progress, then a Status Response action with the BUSY Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.
- If this action is part of a Timed Write transaction, and the Timeout has expired from the preceding Timed Request action, then a Status Response action with the TIMEOUT Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.

NOTE Devices certified prior to 1.4 MAY return UNSUPPORTED_ACCESS for this condition.

- If this action is part of a Timed Write transaction, and this action has TimedRequest set to FALSE, then a Status Response action with the TIMED_REQUEST_MISMATCH Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.

NOTE Devices certified prior to 1.4 MAY return UNSUPPORTED_ACCESS for this condition.

- If this action is marked with TimedRequest as TRUE but this action is not part of a Timed Write transaction (i.e. there was no corresponding Timed Request action prior to it matching the same TransactionID), then a Status Response action with the TIMED_REQUEST_MISMATCH Status Code SHALL be submitted to the message layer and this interaction SHALL terminate.

NOTE Devices certified prior to 1.4 MAY return UNSUPPORTED_ACCESS for this condition.

See [Outgoing Write Response Action](#) for building a Write Response action and executing the Write Request action.

- If this action was unicast and SuppressResponse is FALSE, a Write Response action SHALL be