

with an error status of `CONSTRAINT_ERROR`.

- If the cluster specification defines a following command in response to the command, a [CommandDataIB](#) SHALL be generated for the following command with these fields:
 - CommandFields defined for the following command
 - ClusterPath field of the CommandPath field that is a duplicate of the command path processed, up to the cluster ID
 - Command field of the CommandPath field that is the command ID of the following command
- Else if the cluster specification defines a success or error status as a response (sometimes specified as a Default Response), a [CommandStatusIB](#) SHALL be generated with these fields:
 - CommandPath that is a duplicate of the concrete command path processed
 - Status as defined in the cluster specification
- If the InvokeRequest contains more than 1 [CommandDataIB](#):
 - If the InvokeRequest contains certain commands and endpoints for which the server has an efficient way to process those commands:
 - The server MAY do so, even if this would deviate from the general concept of "execution started in order" for the commands which are grouped.
 - Else:
 - The Invoke Execution SHALL be started for each command in the same order as conveyed and expanded.
 - Actions MAY run concurrently, and the protocol offers no guarantees about completion of one action preceding the start of another.
 - In case one or more of these [CommandDataIB](#) triggers an asynchronous action, any given [Invoke Execution](#) may not complete in the same order as the corresponding [CommandDataIB](#) in the request. As a consequence, the order of generated [CommandDataIB](#) and/or [CommandStatusIB](#) MAY be different from the order of the corresponding [CommandDataIB](#) in the InvokeRequest.
- An [Invoke Response Generation](#) SHALL be performed on completion of all valid commands. A partial [Invoke Response Generation](#) MAY be performed at any time when processing multiple commands, provided it carries at least a single response.

8.8.3. Invoke Response Action

Invoke Response action is a following action for an Invoke Request action. See [Section 8.2.5, “Common Action Behavior”](#) for behavior common to all actions. The specific action information for this action is shown below.

8.8.3.1. Invoke Response Action Information

Action Field	Type	Conformance	Description
SuppressResponse	bool	M	Ignored by client