

Action Field	Type	Conformance	Description
InvokeResponses	list[InvokeResponseIB]	M	command response or status

The SuppressResponse field is mandatory to maintain backwards compatibility with older clients. However, as Matter does not support responses to InvokeResponse actions, this field has no effect.

8.8.3.2. Outgoing Invoke Response Action

- This action SHALL be generated in response to an Invoke Request action, after all valid commands are executed.
- A valid [InvokeResponseIB](#) SHALL only indicate a concrete path.

Invoke Response Generation

- If the previous action in this transaction action is groupcast, this process and transaction terminate with no response.
- Else if SuppressResponse is FALSE, or a [CommandDataIB](#) was generated, an Invoke Response action SHALL be generated as follows:
 - Each generated [CommandStatusIB](#) and [CommandDataIB](#) SHALL be included in an [InvokeResponseIB](#) in the InvokeResponses action field.
 - An Invoke Response action SHALL be submitted to the message layer to send to the source of the previous action.

8.8.3.3. Incoming Invoke Response Action

- Upon receipt of this action, each entry in InvokeResponses SHALL be processed, in order, as follows:
 - If the entry is a [CommandStatusIB](#), it SHALL be submitted to the layer above.
 - Else if the response is a [CommandDataIB](#):
 - If the ClusterPath field of the CommandPath field does not duplicate or match a wildcard of one of the paths in the previous action of the interaction, the entry SHALL be discarded.
 - Else if the command ID value of the Command field of the CommandPath field is not expected by the cluster instance, the entry SHALL be discarded.
 - Else it SHALL be submitted to the layer above.
- For each entry in the initial Invoke Request action that triggered this incoming Invoke Response action, if there isn't a corresponding entry in InvokeResponses, a [CommandStatusIB](#) with the NO_COMMAND_RESPONSE status SHALL be submitted to the layer above.

NOTE

Sending the NO_COMMAND_RESPONSE should only be done after receiving all encoded/transported messages, which indicates that the interaction is completed and the response is missing for those requests.